

APPENDIX A

Commercial Transport Regulations (CTR)

Table I - Axle Spread (Between Extreme Axle Centres)				
	Single Axles and Single Drive Axles	Tandem Axles and Tandem Drive Axles	Tridem Drive Axles	Tridem Axles in Trailer
Truck or Truck Tractor (Power unit only, including Logging Trucks)	Max. 1.0 m	Min. 1.0 m Max. 1.85 m	Min. 2.4 m Max. 2.8 m (Max. 3.1 m ^a)	See specific categories
Truck and Pony Trailer Combinations	Max. 1.0 m	Min. 1.0 m Max. 1.85 m	Min. 2.4 m Max. 2.8 m (Max. 3.1 m ^a)	Min. 2.4 m Max. 2.5 m
Truck and Full Trailer Combinations	Max. 1.0 m	Max. 1.0 m Max. 1.85 m	Min. 2.4 m Max. 2.8 m (Max. 3.1 m ^a)	With tandem drive truck: Min. 2.4 m Max. 3.7 m With tridem drive truck: Min. 2.4 m Max. 3.1 m
Truck Tractor and Semi-Trailer Combinations	Max. 1.0 m	Min. 1.0 m Max. 1.85 m	Min. 2.4 m Max. 2.8 m (Max. 3.1 m ^a)	Min. 2.4 m Max. 3.7 m
A Train	Max. 1.0 m	Min. 1.0 m Max. 1.85 m	Not Applicable	Min. 2.4 m Max. 3.7 m
B Train	Max. 1.0 m	Min. 1.0 m Max. 1.85 m	Min. 2.4 m Max. 2.8 m	With tandem drive truck tractor: Min. 2.4 m Max. 3.7 m With tridem drive truck tractor: Min. 2.4 m Max. 3.1 m
C Train	Max. 1.0 m	Min. 1.0 m Max. 1.85 m	Not Applicable	Min. 2.4 m Max. 3.7 m
Tridem Truck Tractor with Tridem or Tandem Axle Pole Trailer Combinations	Max. 1.0 m	Min. 1.0 m Max. 1.85 m	Min. 2.4 m Max. 2.8 m	Pole Trailer: Min. 2.4 m Max. 3.1 m
Tridem Truck Tractor with Triaxle Pole Trailer Combinations	Max. 1.0 m	Min. 1.0 m Max. 1.85 m	Min. 2.4 m Max. 2.8 m	Pole Trailer: Refer to CTR ^b s. 7.17 Table

^aOilfield bed trucks only

^b CTR is the abbreviation for Commercial Transport Regulations

Table II – Interaxle Spacing (Min. Distances)			
	Single Axle	Tandem Axle	Tridem Axle
Single Axle	3.0 m	3.0 m	3.0 m
Tandem Axle	3.0 m	5.0 m	5.5 m
Tridem Axle	3.0 m	5.5 m	6.0 m