

Minimum Equipment Requirement For All Facilities	Vehicles Inspected
Standard issue domestic/metric hand tools applicable to vehicles and systems to be inspected	All vehicles
Optical headlight aiming device suitable for vehicles being inspected	All motor vehicles
Wheel assembly removal device. In addition facilities licenced 8,200 kg or over must have a device capable of lifting dual wheel assembly	All vehicles
Brake drum and lining/pad measuring tools (only tools specially designed for the purpose acceptable)	All vehicles
Hoisting or lifting device(s) suitable for vehicles being inspected:	
a) overhead/walk-under hoist or pit	a) motor vehicles 5,500 kg and less
b) floor jack hydraulic/pneumatic and jack stands	b) all other vehicles except, motorcycles
Tire tread depth gauge (in 32nds of an inch and millimetres)	All vehicles
Tire pressure gauge	All vehicles
Steering/suspension free play measuring device(s) [KPI tools – dial indicators, Go-No-Go gauges or other tools specifically designed for the use]	All vehicles
Torque wrench (appropriate for wheels/rims inspected)	All vehicles
Gauges for fifth wheel king pin, jaws, and pintle hitch (as required for vehicles being inspected)	All vehicles
Digital voltmeter	Pressure fuel
Digital decibel meter	All Vehicles
Chamber Mate or device for measuring air brake chambers	Vehicles equipped with air brakes
Applicable CSA D250 standards for year of manufacture	School buses

All inspection procedures are visual unless additional inspection procedures are indicated or where applied force is necessary to verify tightness and/or component security.

This page left intentionally blank.

All inspection procedures are visual unless additional inspection procedures are indicated or where applied force is necessary to verify tightness and/or component security.