

Item and Method of Inspection	Reject If
1. Switches	
a) function	a) not malfunctioning as per OEM
b) label	b) not labelled as per CMVSS TSD 123 requirements
2. Horn	
Must be electrically operated. Manually and aurally inspect:	
a) function	a) horn does not work or not securely mounted
b) label	b) not labelled as per CMVSS TSD 123 requirements
3. Mirror(s)	
a) condition	a) missing left side, cracked, clouded, insecure, loose
4. Indicator Lamps	
Test the system to OEM standards.	
a) brake warning indicator	a) not activated as per OEM test design
b) high beam indicator	b) fails to operate
c) turn signal indicator	c) fails to operate, correct indicator does not illuminate for switch selection
d) anti-lock brake indicator (if O.E.M. equipped)	d) fails to operate during test cycle
e) "Check engine" indicator light	e) fails to illuminate or remains illuminated after test cycle
f) neutral indicator	f) fails to operate
	OUT OF SERVICE
	i) Brake failure warning light remains illuminated.

All inspection procedures are visual unless additional inspection procedures are indicated or where applied force is necessary to verify tightness and/or component security.

This page left intentionally blank.

All inspection procedures are visual unless additional inspection procedures are indicated or where applied force is necessary to verify tightness and/or component security.